



Republic of the Philippines
VISAYAS STATE UNIVERSITY
Visca, Baybay City, Leyte

PURCHASE REQUEST

PPMP No. : 150-4-1535-2024-10-0-0	PR No.: TF-2023-11-02916	Date: 11-30-2023
Dept./Office: PCC	Category: Laboratory Equipment	
Section/End-User: Mariles V. Bulawan		
Funding Source: Trust Fund	Project Title/Code: PCC-407/PL480	

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1	Pen type pH Meter	pcs	1	10,000.00	LETUZ M. SUDARIA	10,000.00
Specification:						
	Accuracy (pH)			±0.02		
	Battery Life			250 hr. (average)		
	Calibration			pH, temperature		
	Certifications/Compliance			CE, FCC		
	Display Type			Graphic Dot Matrix		
	Measurement Modes			pH, temperature		
	Resolution (pH)			0.01		
	Includes			Elite pH tester with batteries, lanyard and soft carry case		
	Probe Type			Analog		
	Stability			Stability icon on display		
	Temperature Compensation			Yes		
	Temperature Probe Calibration			1 point		
	Temperature Resolution			0.1°C, 0.1°F		
	Temperature Sensor			Thermistor		
	Dimensions (L x W x H)			200 x 45 x 36mm		
	Backlight Option			Yes		
	Battery Type			4 x AAA Alkaline		
	Calibration Points			1 to 3		
	Description			Elite pH pocket tester for measuring pH with temperature		
	IP Rating			IP 67		
	Range (pH)			-1 to 15		
	Temperature Range (Metric)			0.0°C to 60.0°C		
	Keypad			4 key		
	Relative Humidity Range			5 to 85 %, non-condensing		

Temperature Accuracy $\pm 0.6^{\circ}\text{C}$, $\pm 1.0^{\circ}\text{F}$ for 0.0 to 50.0°C ; $\pm 1.1^{\circ}\text{C}$, $\pm 1.9^{\circ}\text{F}$ for 50.1 to 60.0°C

Temperature (Metric) Operating 5°C to 45°C (ambient)

Temperature Range (English) 32.0°F to 140.0°F

Temperature Selection ATC

Warranty 1 Year for Tester

2	Polypropylene plastic bags	packs	3	200.00		600.00
---	----------------------------	-------	---	--------	--	--------

Specification:

- autoclavable
- dimension: 8x 12
- 100 pcs/ pack

3	Refrigerator, 7.6 cu.ft. 2-Door Inverter	unit	1	27,000.00	LETUZ M. SUDARIA	27,000.00
---	--	------	---	-----------	------------------	-----------

Specification:

- 540x620x1315 : Capacity
- 38kg: Weight
- 7.9 cu ft (223 L) : Dimension
- Liters: 223
- cu ft : 7.9
- FC: 79
- PC: 132
- Product Dimension (W x D x H) mm): 540 x 620 x 1,315
- Defrosting System: Manual w/ Defrost Button
- Standard / Regulation: PNS 396-2:1997
- Energy Consumption (kW/24hr): 0.53
- Net (kg): 38
- Gross (kg): 43
- Voltage: 230V
- Hertz: 60Hz
- Rated Power Input (W): 65 W
- No. of Doors: 2
- Color: Ceramic Gray
- Material: Metal
- Door Pockets: Yes
- Height Adjustable Shelves: Yes
- Sliding 1-2 Shelf-
- Shelf Material: Wire Shelf
- Egg Tray: Yes
- LED Light: Yes
- Power Control: Yes
- Hygiene: Built-in Deodorizer
- Shelves: Yes
- Sliding Material: Wire Shelf
- Ice Box/Tray: Yes
- Quick Freezing: Yes
- Quick Ice Making: Yes

- Energy Savings: Yes
- ECONAVI: Yes
- Compressor: years
- Cooling System: Direct Cooling
- Refrigerant: R600a
- Product Star Rating: 4 Stars
- Energy Efficiency Rating (EER): 380
- Parts & Service: 1 year

TOTAL

37,600.00

Purpose: For PCC-VSU Micro Laboratory use.

Checked by:


ELIZABETH S. QUEVEDO


Funds Available:


NICK FREDDY R. BELLO

TWG - Laboratory Equipment

HEAD, ACCOUNTING OFFICE


Requested by:


MARILES V. BULAWAN

Noted by:


FRANCISCO G. GABUNADA JR.

Approved by:


DAVID LESLIE S. TMS
Vice-PRESIDENT, VSO

Designation:

END USER

UNIT HEAD, PROJECT LEADER