

Republic of the Philippines VISAYAS STATE UNIVERSITY

Visca, Baybay City, Leyte

PURCHASE REQUEST

PR No.: GF-2022-06-00704

Date: 06-02-2022

Dept./Office: DARI

Section/End-User: Jo Jane D. Atok

Category: Construction and Electrical Supplies

Funding Source: General Fund - MOOE

Project Title/Code: ARIC-Generator Shed

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1	Electrical Conduit, (PVC) Orange, 1/2" x 3m	length	15	90.00		1,350.00
2	Electrical Switch, 2-gang, Flush type	pcs	1	200.00		200.00
3	Electrical Tape, Vinyl	rolls	5	70.00		350.00

Specification:

?Flame retardant and compatible with plastic cable and wire harness insulations

?Flexible PVC with aggressive rubber adhesive

?Primary electrical insulation for all wire and cable splices rated up to 600 volts.

?19mm x 16m x 0.155mm

4	Electrical Wire , TF AWG 16 (1.25 mm2), Stranded, 150m/box	box of 50's	1	7,500.00	7,500.00
	Specification:				
	Heat resistant				
	Waterproof				
5	Electrical Wire, THHN / THWN, AWG 10 (5.5mm2), Stranded, 150 meters/box	box of 50's	1	6,200.00	6,200.00
PARTITION OF THE PARTIES.	Specification:				
	?Building Wire				
	OCtronded with Nulan Inculation				
	?Stranded with Nylon Insulation				
	?Gauge 10				

?Stranded with Nylon Insulation

?Gauge 12

?UL listed

7	Electrical, Duplex Convenience Outlet (GFCI)	pcs	2	265.00	530.00
8	Electrical, Junction Box (Octagonal) with cover, PVC	pcs	3	45.00	135.00
9	Electrical, Utility Box, 2" x 4"(Surface Type)	pcs	3	35.00	105.00
10	Emergency Light, 2 x 3 Watts	pcs	1	2,500.00	2,500.00

Specification:

- Good quality
- Durable
- Dome reflector for wider light distribution
- · Automatic Operation (turns on instantly when power is cut-off)
- Equipped with Overcharging protection
- Fuse protected
- Illuminates areas more than 1 lux
- Light Source: 2x1W High Power SMT LED
- Battery: 4V 4.0Ah 6V 4.5Ah Sealed Lead Acid
- Charging Time: <20 hours
- Performance Time:?6 hours (at full charge)

11	Flat Bar, 50mm (3mm thick) x 6m	рс	50	400.00	20,000.00
12	Gravel, 3/4" size	cu.m.	6	1,500.00	9,000.00
13	Heat Detector Alarm System	unit	1	600.00	600.00

Specification:

Two wires conventional 24V DC

Operating Voltage: 9V to 35V DC

Alarm Current: 40 -50mA

Alarm Indication: Red LED ON

Temperature Range: -10C to +50C

Standby Current: 50uA

Humidity range: <95% Relative Humidity

Detecting Range: 50 sq. m @ 6-12 m installation height

Standard/Certification: EN54-5, UL521, GB4716-2005

Dimension: 100mm diameter x 46mm height

	Louver Housing with LED Fluorescent Lamp(2 x 36W), Surface Type	set	2	1,200.00	2,400.00
15	PVC Solvent, 400 cc	pcs	1	250.00	250.00

16	Screened	Sand	cu.m.	18	1,500.00			27,000.00
	Specificat	ion:						
17	Skim Coa	it, 20kg/bag	bag	2	550.00			1,100.00
	Specificati							
	2Good wa	ter vapor permeability						
		t bonding to concrete						
	: LXCellerii	bonding to concrete						
18	Tubular E (1.5mm th	Bar, 50mm x 50mm x6m nick)	рс	4	800.00			3,200.00
19	Tubular E (1.5mm th	Bar, 75mm x 50mm x6m nick)	рс	8	1,300.00			10,400.00
		TOTAL						104,820.00
Pur	pose: For c	office use.						
Che	cked by:	MARLON G/BURL	AS		Funds Available:	Schull ALICIA M.	M guflle FLORES	
TWG - Construction and Electrical Supplies				H	HEAD, BUDGET OFFICE RM& (7)			
	THE RESERVE THE PARTY OF THE PARTY OF THE PARTY.	Requested by:	Noted		et veder internausgebendigt eine geweit in seransport Afrikans beiser zugen der der produktion von der bei der Auf der der beiser der der von der	CONTRACTOR OF THE PROPERTY OF THE PARTY OF T	roved by:	BING
Signa	ature:	1			ntplacts		herry	
Printed Name: JO JAME D. ATOK				MA. TH	HERESA P. LORETO	EDGARDO E. TULIN		
Desig	gnation:	END USER		UNIT HEA	AD, PROJECT LEADER	DJECT LEADER PRESIDENT, VSU		