



## Republic of the Philippines VISAYAS STATE UNIVERSITY

Visca, Baybay City, Leyte

# **PURCHASE REQUEST**

PPMP No.: PPMP-2025-012025-0875

PR No.: GF-2025-01-00064

Date: 01-21-2025

Dept./Office: ICTMC

Category: Office

**Equipment and Appliances** 

Section/End-User: Marco L. Cabras

Funding Source: General Fund - MOOE

Project Title/Code: Emergency Purchase for VSU

Connectivity

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1	Battery Tester/Analyzer	unit	1	2,200.00		2,200.00

#### Specification:

- · Digital Analyzer Tester
- · LCD display
- Type of measurement: CCA, IR, SoC and SOH
- · Multi battery type: AGM, GEL, STD, Lead Acid,
- 12V/24V Battery
- 1 year warranty

	THE WAR STREET				17 000 00
2	Battery, LiFePO4	unit	2	8,500.00	17,000.00

#### Specification:

- 12 volts
- 20 Ah
- . Nominal Capacity: 20ah 0.2 C
- Cycle Life:> 4000 Cycles at 0.2 ?; End-of-Life Capability
- · Charging Voltage: 14.6±0.2V
- · Charger Current: 4A
- Maximum Charging Current: 10.0
- · Discharge Current: 4A
- . Maximum Current Duration: 20A . Discharge Cut-off Voltage: 10.0V
- · Shell Material: ABS
- Size (L/Ft/H):180-200mm\*75-80mm \* 170-185mm

- 1						
Ī	3	Oil Filter C-206	pc	1	800.00	800.00

Specification:

OEM No.

15208-W1111

15208-W1116

4 Sealed Lead Acid Battery (VRLA) unit 4 3,000.00 12,000.00

#### Specification:

- 12 volts, 20 Ah
- Size (L/Ft/H):180-200mm\*75-80mm \* 170-185mm
- Maintenance Free
- Rechargeable
- Good Quality
- · Authentic/ Original

-		7				
5	Smart Battery Charger, 12V/24V, 25A/15A	unit	2	5,000.00	10,000.	00

### Specification:

- . Compatible type of battery: Lead Acid, AGM GEL, LiFePO4
- Intelligent Multiple Protection: Over heat protection, Overcurrent protection, electric shock protection, short circuit
  protection, reverse connect protection, overvoltage protection, Low voltage protection and fire protection.
- Multi Stage automatic charging: 1-Stage: Battery desulphation, 2-stage: Soft start charge, 3-stage: Bulk charge, 4-stage: Absorption charge, 5-stage: Battery test, 6-stage: Recondition charge, Stage-7: Float & maintenance charging, 8-stage: Re-start charge after battery discharged.
- Input voltage: 100-240V AC, 50-60Hz
- Rated output: 12V 25A, 24V 15A
- · Battery Range: 5-400Ah
- · Compliant standards: CE, FCC, UKCA
- · Colored Digital display indicator
- With Booster Mode
- · US Plug type (AC)
- 1 year warranty

	TOTAL			42,000.0
Purpose: Eme	rgency Purchase for VSU Net	work Connectivity		
Checked by:	NORMAN O. VILLAS			CIA M. FEORES NAM-107
	WG - Office Equipment and A		HEAL	
Signature: Printed Name:	MARCO L. CABRAS		VILLAGONŽALO	Approved by: PROSE IVY G. YEPES
Designation:		UNIT HEAD.	PROJÉCT LEADER	PRESIDENT, VSU