

Scan Here



PR-2022-0620-39559

CAN HERE



PR-2022-0602-36081

With no release to OP



Republic of the Philippines
VISAYAS STATE UNIVERSITY
 Visca, Baybay City, Leyte

PURCHASE REQUEST

PR No.: GF-2022-06-00713

Date: 06-02-2022

Dept./Office: **ODPP**Category: **Electronics
supplies**Section/End-User: **Rafael Rosario A. Juntilla**Project Title/Code: **PPES/PPO-2022**Funding Source: **General Fund - MOOE**

Item #	Item Description	Unit	Qty	Unit Cost	PAR/ICS	Total Cost
1	1/4" Male Phone Str Mono Plug	pcs	20	400.00		8,000.00
Specification: <ul style="list-style-type: none"> Male 1/4" Phone Str Mono Nickel Number of positions (w/o PE): 2 Rated current (40 °C) (A): 75 Rated voltage (V): 25 						
2	3.5 mm 2-Pole Mono Phone Plug Connector	pcs	20	200.00		4,000.00
Specification: <ul style="list-style-type: none"> Diecast Shell For Cables 2.5 to 5mm Diameter Precision-Machined Contacts Quick Assembly 3 Piece Design 						
3	Adjustable Professional Tripod Lighting Stand	unit	4	7,000.00		28,000.00
Specification: <ul style="list-style-type: none"> Adjustable Professional Tripod Stand (black) Heavy Duty, Stable and sturdy Light can stand can easily assembled Can attach up to 4 lighting fixtures Tripod legs can be adjusted Tripod light stand height: approx. 122 cm with 2 more poles to extend height of the light stand Light stand height can be extended to up approx. 210 cm For lighting setups for any events 						
4	Battery Charger for AA and AAA with 4 AA NiMH rechargeable batteries included	unit	2	2,500.00		5,000.00
Specification: <ul style="list-style-type: none"> Overcharge Protection: Limits damage to batteries from overcharge 						

- Safety Shut Off: Safety timer ensures charger is not active for extended periods of time
- Bad Battery Detection: LED light will flash red when bad battery or non-rechargeable battery placed in the charger.
- Easy-to-read LED displays charging status
- Red = Charging, Green = Good to Go!
- "Bad battery" indicator light
- Recharges 2 or 4 AA or AAA NiMH rechargeable batteries in 5 hours
- With 4 AA NiMH Batteries included

5	Crank Up Lighting stand	unit	2	13,000.00		26,000.00
---	-------------------------	------	---	-----------	--	-----------

Specification:

- Crank Up Lighting Stand
- Features the Quick-N-Easy Gear Up for fast and easy adjustment.
- All aluminum tubes and steel T-bar with clip for easy mounting construction reinforces and strengthens without excess weight.
- Quick-N-Easy Gear Up for fast and simple adjustment square steel T-bar tubing for strength.
- Length: 164-350cm(64.6-137.8")
- Base diameter: 72.4"
- Load capacity: 45 kg folded size

6	DMX 512 Intelligent Lighting Controller	unit	1	9,000.00		9,000.00
---	---	------	---	----------	--	----------

Specification:

- Control up to 192 DMX Channels
- 30 banks, each composed of 8 Programmable scenes.
- 8 adjustable potentiometer to adjust the output size.
- Built-in MIC head, and voice features.
- Automatically trigger state, the TAP SYNC button or the SPEED potentiometer to determine automatically trigger time.
- MIDI interface, may at any time using the MIDI signal control.
- 4 LED digital display.
- The first LED digit shows CHASES, the second digit led shows SCENES
- The third and fourth led digit shows BANKS.
- The second, third, fourth led digit show steps 0-255 or TIME.
- BLACK OUT function can be used manually or MIDI remote control.
- CHASES programming and CHASES run function can be used manually or MIDI remote control.
- Output delay function, the FADE TIME potentiometer to adjust the delay time.
- DMX output polarity selection.

7	Flight Case LED Par 8s	unit	4	8,500.00		34,000.00
---	------------------------	------	---	----------	--	-----------

Specification:

- Fits for 8 pcs LED PAR Lights
- Heavy Duty Honeycomb Design
- Twist Lock
- Heavy Duty Wheels
- Aluminum Corners

8	Jack Connector 6.35 mm Cable Mount Stereo Plug, 3Pole 10A	pcs	20	400.00		8,000.00
---	---	-----	----	--------	--	----------

Specification:

- Male, 6.35 mm
- Cable Mount
- Type: Stereo
- Body Orientation: Straight
- Termination Method: Solder
- Contact Plating: Nickel
- Current Rating: 10A
- Housing Material: Zinc Alloy
- Contact Material: Brass
- No of Poles/ Way: 3

9	Power Controller 10 Channel Audio	unit	1	3,000.00		3,000.00
---	--	------	---	----------	--	----------

Specification:

- Power Controller 10 Channel Titanium audio
- 10 lighted switches on front panel
- 15 amps. resettable circuit breaker on front panel
- 8 grounded AC sockets on rear of the unit
- Maximum load: 15 amps 0r 1800 watts

10	Stage Light Outdoor RGB 18 x 18 flat Par LED Mini	set	8	7,000.00		56,000.00
----	--	-----	---	----------	--	-----------

Specification:

- Stage Light Outdoor RGB 18 x 18 Flat Par LED mini 64 warm White
- Color Temperature: 3500k(warm White)

11	Stage Lights Bar, Yeessite 72W 24LEDs RGB Wash Lights DMX Control LED	set	8	5,500.00		44,000.00
----	--	-----	---	----------	--	-----------

Specification:

Stage Lights Bar, 72W 24LEDs RGB Wash Lights DMX LED Wall Washer Light Uplight

40 inch Long Professional grade indoor linear bar powered 24x3-Watt LEDs

Light Source: 24 TRI LEDs(RGB)






Power Draw: 72 watts

40- degree beam angle provides vibrant and broad light beam to wash stage, wall and dance floor

Power Linking: Max 10 units at 120 Volts or 27 units at 230Volts

12	Transmitter Receiver Kit portable (4 pcs)	pcs	2	6,500.00		13,000.00
----	--	-----	---	----------	--	-----------

Specification: <ul style="list-style-type: none"> • Transmitter Receiver Kit Portable 2.4G ISM Wireless Stage Light lighting fixtures • High effective GFSK module, communication design; 126 channels jumping frequency automatically, high • anti-jamming ability, to ensure that works reliability 						
13	Waterproof LED Parabolic Aluminized Reflector (PAR) Lights for Stage Events	set	20	3,000.00		60,000.00
Specification: <ul style="list-style-type: none"> • Light Source:18X18w RGBWA • Beam Angle: 25 Degree • Waterproof: IP65 • Housing: Aluminum • Style :DMX Stage Light • Power:300W • Color: 6000k(daylight) 						
14	Wireless Microphone Mic System, 2.4G, 6 channels	unit	2	15,000.00		30,000.00
Specification: <ul style="list-style-type: none"> • 2.4G wireless Microphone Mic System 6 channels XLR Connection Built-in Rechargeable Lithium Battery • Compact size 2.4G wireless microphone system, XLR connection, easy to use • less than 4ms ultra-low latency, clear and stable signal transmission • 32bit/48Khz high resolution audio quality • Built -in rechargeable lithium battery 						
15	XLR 3 Pole Female, Stamped Contacts, Nickel Finish	pcs	60	300.00		18,000.00
Specification: <ul style="list-style-type: none"> • XLR 3 pole female, stamped contacts, nickel finish. • Ergonomic stylish sleeve design for improved grip. • Oversized latch lever preserves your thumb. Leading first mate last break pin 1 on socket connectors. • Chuck style cable clamp to suit 3mm - 8mm (0.118" - 0.314") cable. • Overmolded cable support boot • Precision machined pin contacts • Compact 2.5mm (14AWG) solder buckets • Zinc diecast shell housing with Satin nickel finish. 						
16	XLR male connector	pcs	60	500.00		30,000.00
Specification: <ul style="list-style-type: none"> • Standard XLR Male 3pin • Nickel Contact Plating • Mating Cycles: 1000 Cycle 						
	TOTAL					376,000.00
Purpose: For PPES Personnel's equipment						

Checked by:  MICHAEL ANTHONY JAY B. REGIS		Funds Available:  ALICIA M. FLORES	
TWG - Electronics supplies		HEAD, BUDGET OFFICE <i>Sam. by AM</i>	
Signature: 	Requested by: RAFAEL ROSARIO A. JUNTILLA	Noted by: 	Approved by: <i>Sam. by AM</i> 
Printed Name:	RAFAEL ROSARIO A. JUNTILLA	MARLON G. BURLAS	EDGARDO E. TULIN
Designation:	END USER	UNIT HEAD, PROJECT LEADER	PRESIDENT, VSU